John E. Keba
Rotating Machinery Analysis Group
Rocketdyne Division
Boeing North American, Inc.

Seal/Secondary Air Delivery Workshop NASA - Glenn Research Center October 29, 1999





8185864465

OCT-26 99 Ø5:13



- Introduction -- Rocket Turbomachinery Shaft Seals
- Inter-Propellant-Seal (IPS) Systems
- 'Lift-off' Seal Systems
- **Technology Development Needs**
- **Rocket Engine Characteristics**
- Engine cycles, propellants, missions, etc.

۲,

- Influence on shaft sealing requirements
- Conclusions

FROM: ROCKETDYNE



8185864465

OCT-26 99 Ø5:13

FROM: ROCKETDYNE




- **IPS Purpose**
- Separate incompatible fluids
- Limit propellant leakage
- Technology advancement needs
- Reduction or elimination of buffer gas consumption
- Reduce or eliminate drain requirements Reduced length of seal system
- Higher allowable seal surface velocities






8185864465




8185864465



- Purpose
- Prevent propellant leakage into turbine before start and after cut-off
- Limit leakage into turbine during operation
- Technology advancement needs
- Reduction in seal system length (all-in-one seal)
- Elimination of overboard drain/vent line


Eax + 729-224.8220 Exx 818 289-7492	Phone 7.544. 4529 Phone 5 586-1565	To Hoth mount	- }	7671
Ext \$ 18-285-4762	Phone 586-1565	CO BROING - CAMECH	From SUSIC UNLINES	Date 10/1/ Ap pages 16







8185864465





Slide 8

Upper Stage

Single Stage-to-Orbit

Booster

# **Rocket Engine Classifications**

## **Engine Cycle**

'Open' Cycle

- Gas Generator
- Expander Bleed
- Staged Combustion
- Fuel Rich

## 'Closed' Cycle

### LOX Rich

Mission

## **Propellants**

Cryogenic

- •LOX -- LH2
- LOX -- Kerosene

Storable

- •NTO -- MMH, UDMH, etc..
- H2O2 -- Kerosene

### Other

Man Rated Vs Non-Man Rated Expendable Vs. Reusable

O BOEING

Slide 9

PAGE.04 OCT 26 '99 11:07 8185864465

# Cycle defined by fluid source used to drive turbines

'Open' Cycle -- Turbine drive gas exhausted downstream of Main Combustion Chamber (MCC)

- Gas Generator Cycle -- Fuel-rich combustion products
- Expander Bleed Cycle -- Propellant, vaporized and heated by MCC exhaust

Influence on shaft seals:

- Relatively low turbine cavity pressures
- Impulse turbine -- low turbine flow rate effected by seal leakage

'Closed' Cycle

Staged Combustion - Partial combustion of propellants, turbine exhausts into MCC injector

Influence on shaft seals:

- Very high pressure in turbine cavity
- Relatively high turbine flow rate compared to seal leakage

Rocketdyne
Propulsion & Power



FROM: ROCKETDYNE

Booster

High thrust -- high propellant flowrates, large pumps

Weight and performance less critical than upperstage and STO

Upper Stage

 Weight and performance critical Low thrust -- low flowrates, small pumps Restart requirement

•ST0

Wide throttle range, large pumps

Weight and performance very critical


Post-if Fax Note Phone \$ 256.544.4529 Fax " 256-564.875a 7671 Date 10/10/19 pages Fax 181 8 586-4465

Slide 11

Ø BOEING

Rocketdyne Propulsion & Power

Rocketdyne Propulsion & Power





OCT 26 '99 11:10

8185864465

Rocketdyne Propulsion & Power





8185864465